

Fuel and Emission — Section 11

	MEASUREMENT	STANDARD (NEW)
Pressure regulator	Pressure kPa (kg/cm ² , psi)	330-370 (3.30-3.70, 47-53)
Fuel tank	Capacity ℓ (US gal, Imp gal)	70 (18.5, 15.4)
Engine	Fast idle rpm	1,100-1,900
	Idle speed rpm (with headlight and cooling fan off)	800 ± 50 (M/T: neutral) 780 ± 50 (A/T: N or P position)
	Idle CO % max.	0.1

Clutch — Section 12

	MEASUREMENT	STANDARD (NEW)	SERVICE LIMIT
Clutch pedal	Pedal height	to floor	176.2 (6.94)
	Stroke		125 (4.92)
	Pedal play		9-15 (0.35-0.59)
	Disengagement height	to floor	92 (3.62) min.
Pressure plate	Warpage		0.03 (0.001) max. 0.15 (0.006)
1st clutch disc	Thickness		8.3-9.0 (0.33-0.35)
	Rivet head depth		1.1 (0.04) min. 0.2 (0.01)
2nd clutch disc	Thickness		7.6-8.3 (0.30-0.33)
	Rivet head depth		1.1 (0.04) min. 0.2 (0.01)
Mid plate	Warpage		0.05 (0.002) max. 0.15 (0.006)
Flywheel	Clutch surface runout		0.05 (0.002) max. 0.15 (0.006)