

Trunk Lid Spoiler/Trunk Trim Panel

Replacement

NOTE:

- Take care not to scratch the trunk lid.
- Take care not to bend or scratch the trim panels.

CAUTION: When prying with a flat tip screwdriver, wrap it with protective tape or a shop towel to prevent damage.

HIGH-MOUNT BRAKE LIGHT

Carefully pry out the caps with a flat tip screwdriver, and remove the mounting screws.

Disconnect the connector.

TRUNK LID SPOILER

Remove the trunk lid spoiler mounting nuts, then pull the trunk lid spoiler up.

MOUNTING SCREW

CAP

HIGH-MOUNT BRAKE LIGHT HARNESS

TRUNK LID

WEATHERSTRIP

ADHESIVE TAPE

NOTE: Clean the trunk lid bonding surface with a sponge dampened in alcohol.

TRUNK LID SPOILER MOUNTING NUTS

☆ 6 x 1.0 mm
10 N-m (1.0 kg-m, 7.2 lb-ft)

SCREW

CLIP (5)

LEFT TRUNK SIDE TRIM PANEL

Pry out the clips.

RIGHT TRUNK SIDE TRIM PANEL

Pry out the clips.

Disconnect the connector.

CLIP (10)

TRUNK FLOOR TRIM PANEL

Pry out the clips and loosen the screws, then pry out the clips.

HOOK

TRUNK FLOOR TRIM PANEL

HOOK

WEATHERSTRIP

WEATHERSTRIP

Installation is the reverse of the removal procedure.

NOTE:

- If necessary, replace any damaged clips.
- Make sure the connector is connected properly.

☆: CORROSION RESISTANT NUT